

21423 Winsen (Luhe) - Germany

Telefon: +49 (0)4171 / 8480-0 Homepage: www.ampri.de e-mail: info@ampri.de

Technical Data Sheet


Article-No.: 01172

EN

Description: **STYLE Graphite**

Nitrile examination glove

graphite, non sterile, powder free





PRODUCT DESCRIP	TION						
material	☐ Latex	✓ Nitrile	□ Vinyl	☐ Vinyl-Nitrile-	☐ Polyethy-lene	☐ TPE	□ cotton
				mixture	(PE)		
colour	white	blue	black	☐ mint	☐ purple	☐ mix	graphite
characteristics	prepowdered	powderfree	☐ sterile	non sterile	☑ ambidex-	☐ fits hand-	☐ accelerator-
					trous	specific	free
surface		☐ not textured	embossed				
SIZES							
	XS (5-6)	S (6-7)	M (7-8)	L (8-9)	XL (9-10)	XXL (10-11)	XXXL (11-12)
width	≤ 80 mm	80 ± 10 mm	95 ± 10 mm	110 ± 10 mm	115 ± 10 mm	-	-
length	≥ 240 mm	≥ 240 mm	≥ 240 mm	≥ 240 mm	≥ 240 mm	-	-
REGULATORY AFFA	IRS						
PPE-Regulation	☐ Category I	☐ Category II	✓ Category III	no PPE-article			
(EU) 2016/425		cutego. y	catego.,				
MD-Regulation	☑ Class I	Class II a	☐ Class III	sterile	☐ measuring	no medical	((
(EU) 2017/745					function	device	CE
Food Contact	☑ acidic foods	☑ aqueous		☑ alcoholic	✓ dry foods	not approved	
(EG) 1935/2004		foods	,	foods	,	for food-	527
, , ,						contact	JC1
	l .	ı	I.				
STANDARDISATION							
EN 388 Mechanical	abrasion	blade cut	tear resistance	puncture	blade cut	impact test	
Risks	resistance	resistance		resistance	resistance		
	and a self-relati	Coupe-Test			TDM-Test		
Level	not applicable						
Level EN 374-1		Coupe-Test che	mical	100000	TDM-Test code		
	Sodium hydroxide	Coupe-Test che	mical		TDM-Test	(ISO 374-1/Type B
EN 374-1	Sodium hydroxide Hydrogen Peroxid	Coupe-Test che 40% e 30%	mical		TDM-Test code	(ISO 374-1/Type B
EN 374-1 Chemical Risks EN 374-4	Sodium hydroxide	Coupe-Test che 40% e 30%	mical		TDM-Test	(ISO 374-1/Type B
EN 374-1 Chemical Risks	Sodium hydroxide Hydrogen Peroxid	Coupe-Test che 40% e 30%	mical		TDM-Test code	(ISO 374-1/Type B
EN 374-1 Chemical Risks EN 374-4	Sodium hydroxide Hydrogen Peroxid	Coupe-Test che 40% e 30%	mical		TDM-Test code	(
EN 374-1 Chemical Risks EN 374-4 Degradation	Sodium hydroxide Hydrogen Peroxid Formaldehyde 379	che 40% e 30%			Code		KPT
EN 374-1 Chemical Risks EN 374-4 Degradation EN 374-5	Sodium hydroxide Hydrogen Peroxid Formaldehyde 379	che 40% e 30%			TDM-Test code		KPT 8N 850 374-5-2016
EN 374-1 Chemical Risks EN 374-4 Degradation EN 374-5 microorganism	Sodium hydroxide Hydrogen Peroxid Formaldehyde 379	che 40% e 30%			Code		KPT
EN 374-1 Chemical Risks EN 374-4 Degradation EN 374-5 microorganism tightness	Sodium hydroxide Hydrogen Peroxid Formaldehyde 375 The glove is tight a	che 40% e 30% %	sms (viral, bacteria a	and fungi). Test acco	Code		KPT 88.150.378-52018
EN 374-1 Chemical Risks EN 374-4 Degradation EN 374-5 microorganism tightness	Sodium hydroxide Hydrogen Peroxid Formaldehyde 375 The glove is tight a	che 40% e 30%	sms (viral, bacteria a	and fungi). Test acco	Code		KPT 88.150.378-52018
EN 374-1 Chemical Risks EN 374-4 Degradation EN 374-5 microorganism tightness	Sodium hydroxide Hydrogen Peroxid Formaldehyde 375 The glove is tight a	che 40% e 30% %	sms (viral, bacteria a	and fungi). Test acco	Code		KPT 88.150.378-52018
EN 374-1 Chemical Risks EN 374-4 Degradation EN 374-5 microorganism tightness EN ISO 21420 protective gloves	Sodium hydroxide Hydrogen Peroxid Formaldehyde 375 The glove is tight a	che 40% e 30% % against microorganis	oms (viral, bacteria a	and fungi). Test acco	rding to ISO 16604 -	method B.	KPT 6N 150 374-5-2016 VIRUS
EN 374-1 Chemical Risks EN 374-4 Degradation EN 374-5 microorganism tightness EN ISO 21420 protective gloves EN 455	Sodium hydroxide Hydrogen Peroxid Formaldehyde 375 The glove is tight a	che 40% e 30% % against microorganis	oms (viral, bacteria a	and fungi). Test acco	Code	method B.	KPT IN 150 374-5-2016 WIRUS EN
EN 374-1 Chemical Risks EN 374-4 Degradation EN 374-5 microorganism tightness EN ISO 21420 protective gloves	Sodium hydroxide Hydrogen Peroxid Formaldehyde 375 The glove is tight a	che 40% e 30% % against microorganis	oms (viral, bacteria a	and fungi). Test acco	rding to ISO 16604 -	method B.	KPT 6N 150 374-5-2016 VIRUS
EN 374-1 Chemical Risks EN 374-4 Degradation EN 374-5 microorganism tightness EN ISO 21420 protective gloves EN 455 medical gloves for	Sodium hydroxide Hydrogen Peroxid Formaldehyde 375 The glove is tight a The glove meets ti	che 40% e 30% % egainst microorganis ne requirements acc	oms (viral, bacteria a cording to EN ISO 21 cording to EN 455-1	and fungi). Test acco	rding to ISO 16604 -	method B. break ≥ 3.6 N.	KPT 6N 50 374-52016 WRUS EN 455
EN 374-1 Chemical Risks EN 374-4 Degradation EN 374-5 microorganism tightness EN ISO 21420 protective gloves EN 455 medical gloves for single use	Sodium hydroxide Hydrogen Peroxid Formaldehyde 375 The glove is tight a The glove meets ti	che 40% e 30% % against microorganis ne requirements acc	oms (viral, bacteria a cording to EN ISO 21 cording to EN 455-1	and fungi). Test acco	rding to ISO 16604 -	method B. break ≥ 3.6 N.	KPT 8N 50324-52016 VIRUS EN 455
EN 374-1 Chemical Risks EN 374-4 Degradation EN 374-5 microorganism tightness EN ISO 21420 protective gloves EN 455 medical gloves for single use EN 455-1	Sodium hydroxide Hydrogen Peroxid Formaldehyde 375 The glove is tight a The glove meets ti The glove meets ti	che 40% e 30% % against microorganis ne requirements acc	oms (viral, bacteria a cording to EN ISO 21 cording to EN 455-1	and fungi). Test acco	rding to ISO 16604 -	method B. break ≥ 3.6 N.	KPT 6N 50 374-52016 WRUS EN 455
EN 374-1 Chemical Risks EN 374-4 Degradation EN 374-5 microorganism tightness EN ISO 21420 protective gloves EN 455 medical gloves for single use EN 455-1	Sodium hydroxide Hydrogen Peroxid Formaldehyde 375 The glove is tight a The glove meets ti The glove meets ti The glove has an A general Inspection	che 40% e 30% % against microorganis ne requirements acc	oms (viral, bacteria a cording to EN ISO 21 cording to EN 455-1	and fungi). Test acco	rding to ISO 16604 -	method B. break ≥ 3.6 N.	KPT 8N 50324-52016 VIRUS EN 455
EN 374-1 Chemical Risks EN 374-4 Degradation EN 374-5 microorganism tightness EN ISO 21420 protective gloves EN 455 medical gloves for single use EN 455-1 freedom from holes	Sodium hydroxide Hydrogen Peroxid Formaldehyde 375 The glove is tight a The glove meets ti The glove meets ti	che 40% e 30% % against microorganis ne requirements acc	oms (viral, bacteria a cording to EN ISO 21 cording to EN 455-1	and fungi). Test acco	rding to ISO 16604 -	method B. break ≥ 3.6 N.	KPT 8N 50324-52016 VIRUS EN 455
EN 374-1 Chemical Risks EN 374-4 Degradation EN 374-5 microorganism tightness EN ISO 21420 protective gloves EN 455 medical gloves for single use EN 455-1 freedom from holes EN 16350	Sodium hydroxide Hydrogen Peroxid Formaldehyde 375 The glove is tight a The glove meets ti The glove meets ti The glove has an A general Inspection	che 40% e 30% % against microorganis ne requirements acc	oms (viral, bacteria a cording to EN ISO 21 cording to EN 455-1	and fungi). Test acco	rding to ISO 16604 -	method B. break ≥ 3.6 N.	KPT 8N 50324-52016 VIRUS EN 455

QMFORM_60.003 1/3 issue date: 16.04.2025



21423 Winsen (Luhe) - Germany Telefon: +49 (0)4171 / 8480-0

Homepage: www.ampri.de e-mail: info@ampri.de

Technical Data Sheet

Article-No.: **01172**

Description: STYLE Graphite

Nitrile examination glove

graphite, non sterile, powder free

generell information			
material	carton		
pieces per subpacking	100		
GTIN subpacking size XS	4044941734316		
GTIN subpacking size S	4044941734430		
GTIN subpacking size M	4044941734354		
GTIN subpacking size L	4044941734378		
GTIN subpacking size XL	4044941734392		
GTIN subpacking size XXL	-		
GTIN subpacking size XXXL	-		
PZN subpacking size XS	19149029		
PZN subpacking size S	19149041		
PZN subpacking size M	19149058		
PZN subpacking size L	19149064		
PZN subpacking size XL	19149070		
PZN subpacking size XXL	-		
PZN subpacking size XXXL	-		
measures & size			
length	215 mm		
width	120 mm		
heigth	60 mm		
weights			
size	gross weight*		
XS	380 g		
S	410 g		
M	430 g		
L	460 g		
XL	500 g		
XXL	-		
XXXL	-		

LOGISTIC DATA PALETTE	
general information	
kind of palett	euro-palette
measures & size	
cartons per layer	10
layers per palette	8
heigth of the palette	199 cm
weights	
size	gross weight*
XS	369 kg
S	393 kg
M	409 kg
L	433 kg
XL	465 kg
XXL	-
XXXL	-

EN



generell information			
material	carton		
subpackings per outer packing	10		
GTIN outer packing size XS	4044941734323		
GTIN outer packing size S	4044941734347		
GTIN outer packing size M	4044941734361		
GTIN outer packing size L	4044941734385		
GTIN outer packing size XL	4044941734408		
GTIN outer packing size XXL	-		
GTIN outer packing size XXXL	-		
PZN outer packing size XS	-		
PZN outer packing size S	-		
PZN outer packing size M	-		
PZN outer packing size L	-		
PZN outer packing size XL	-		
PZN outer packing size XXL	-		
PZN outer packing size XXXL	-		
measures & size			
length	315 mm		
width	255 mm		
heigth	230 mm		
weights			
size	gross weight*		
XS	4.300 g		
S	4.600 g		
M	4.800 g		
L	5.100 g		
XL	5.500 g		
XXL	-		
XXXL	-		



AMPri Handelsgesellschaft mbH

Benzstraße 16

21423 Winsen (Luhe) - Germany Telefon: +49 (0)4171 / 8480-0

> Homepage: www.ampri.de e-mail: info@ampri.de

Technical Data Sheet

Article-No.: 01172

Description: STYLE Graphite

Nitrile examination glove

graphite, non sterile, powder free



WARNINGS AND SAFETY INFORMATION

storage / expiry date

Store gloves in original packaging in a cool and dry place without additional weight, protect from direct sunlight. Do not store near ozone sources (laser printers, copiers). The actual expiry time in use cannot be specified in general terms, as it depends on the general conditions of use. An individual risk assessment must be carried out in each case. The expiry date - valid for proper storage - is stated on the packaging.

use and control

Always use protective gloves only for the intended use and in the correct size. A check/risk assessment must be carried out to ensure that the gloves are suitable for the intended use, as the conditions at the workplace may deviate from those of the type test depending on temperature, abrasion and degradation. Breakthrough times and permeation levels are based on laboratory measurements and are determined using samples taken from the palm of the hand. The actual duration of protection of a glove with a specific substance can vary significantly due to the conditions of use (temperature, abrasion, stretching). In the case of aggressive chemicals, degradation (change in mechanical properties) can be an important factor to consider when selecting chemical-resistant gloves. This information does not reflect the actual duration of protection in the workplace and the distinction between mixtures and pure chemicals. The chemical resistance was determined under laboratory conditions only on the basis of samples from the palm and refers only to the chemicals tested. The situation may be different if the chemical is used in a mixture. The penetration resistance was evaluated under laboratory conditions and refers only to the tested specimen. The degradation results according to EN ISO 374-4 show the change in puncture resistance of the gloves after exposure to the tested chemical.

Before use, the gloves must be checked for holes or damage.

disposal

Used gloves must be disposed of after contact with chemicals in accordance with the disposal regulations for the chemical and the regulations of the local waste disposal company. Unused gloves can be disposed of with household waste.

disinfection

Disinfection is not intended for these gloves and is the responsibility of the user.

warnings/ allergy information

Protective gloves are intended for single use only.

This product contains dithiocarbamates, which may cause allergic reactions

donning and doffing instructions











*slight deviations possible due to standard tolerances

rev-no.: 2025-01 date 11.06.2025

changes and errors excepted

QMFORM_60.003 issue date: 16.04.2025