

21423 Winsen (Luhe) - Germany

Telefon: +49 (0)4171 / 8480-0 Homepage: www.ampri.de e-mail: info@ampri.de




4MPri

Article-No.: 01176

EN

Description: **STYLE CEDRO**

> Nitrile examination glove cedro, non sterile, powder free





PRODUCT DESCRIP	HON						
material	☐ Latex	✓ Nitrile	□ Vinyl	☐ Vinyl-Nitrile-	☐ Polyethy-lene	☐ TPE	cotton
				mixture	(PE)		
colour	white	blue	black	☐ mint	☐ purple	mix	✓ cedro ✓ cedro
characteristics	prepowdered	powderfree	☐ sterile	non sterile	☑ ambidex-	fits hand-	☐ Aloe Vera
					trous	specific	inner coating
surface		☐ not textured	embossed				
SIZES							
	XS (5-6)	S (6-7)	M (7-8)	L (8-9)	XL (9-10)	XXL (10-11)	XXXL (11-12)
width	≤ 80 mm	80 ± 10 mm	95 ± 10 mm	110 ± 10 mm	115 ± 10 mm	-	-
length	≥ 240 mm	≥ 240 mm	≥ 240 mm	≥ 240 mm	≥ 240 mm	-	-
REGULATORY AFFA	IRS						
PPE-Regulation	☐ Category I	☐ Category II	✓ Category III	☐ no PPE-article			
(EU) 2016/425							
MD-Regulation	☑ Class I	☐ Class II a	☐ Class III	□ sterile	☐ measuring	no medical	CE
(EU) 2017/745					function	device	CE
Food Contact	☑ acidic foods	☑ aqueous	✓ fatty foods	☑ alcoholic	☑ dry foods	☐ not approved	
(EG) 1935/2004		foods		foods		for food-	5217
						contact) .
CTANDARDICATION		I	I				
STANDARDISATION							
EN 388 Mechanical	abrasion	blade cut	tear resistance	puncture	blade cut	impact test	
Risks	resistance	resistance		resistance	resistance		
		Coupe-Test			TDM-Test		
Lavial	not applicable						
Level	not applicable						
EN 374-1			mical		code		
	Sodium hydroxide	40%	mical		ŀ	(ISO 374-1/Type B
EN 374-1 Chemical Risks	Sodium hydroxide Hydrogen Peroxid	40% e 30%	mical		ŀ	(ISO 374-1/Type B
EN 374-1 Chemical Risks EN 374-4	Sodium hydroxide	40% e 30%	mical		ŀ	(ISO 374-1/Type B
EN 374-1 Chemical Risks	Sodium hydroxide Hydrogen Peroxid	40% e 30%	mical		ŀ	(ISO 374-1/Type B
EN 374-1 Chemical Risks EN 374-4	Sodium hydroxide Hydrogen Peroxid	40% e 30%	mical		ŀ	(
EN 374-1 Chemical Risks EN 374-4 Degradation	Sodium hydroxide Hydrogen Peroxid Formaldehyde 379	40% e 30% %		and fungi). Test acco	F	-	KPT
EN 374-1 Chemical Risks EN 374-4 Degradation EN 374-5	Sodium hydroxide Hydrogen Peroxid Formaldehyde 379	40% e 30% %		and fungi). Test acco	ŀ	-	KPT 50 134 5-2016
EN 374-1 Chemical Risks EN 374-4 Degradation EN 374-5 microorganism	Sodium hydroxide Hydrogen Peroxid Formaldehyde 379	40% e 30% %		and fungi). Test acco	F	-	KPT
EN 374-1 Chemical Risks EN 374-4 Degradation EN 374-5 microorganism tightness	Sodium hydroxide Hydrogen Peroxid Formaldehyde 375 The glove is tight a	40% e 30% % sgainst microorgani	sms (viral, bacteria a		F	-	KPT 6N 150 374 5-2016
EN 374-1 Chemical Risks EN 374-4 Degradation EN 374-5 microorganism tightness	Sodium hydroxide Hydrogen Peroxid Formaldehyde 375 The glove is tight a	40% e 30% % sgainst microorgani			F	-	KPT 6N 150 374 5-2016
EN 374-1 Chemical Risks EN 374-4 Degradation EN 374-5 microorganism tightness	Sodium hydroxide Hydrogen Peroxid Formaldehyde 375 The glove is tight a	40% e 30% % sgainst microorgani	sms (viral, bacteria a		F	-	KPT 6N 150 374 5-2016
EN 374-1 Chemical Risks EN 374-4 Degradation EN 374-5 microorganism tightness	Sodium hydroxide Hydrogen Peroxid Formaldehyde 375 The glove is tight a	40% e 30% % against microorganione requirements acc	sms (viral, bacteria a	1420	F	method B.	KPT EN ISO 375-5-2016 WIRUS
EN 374-1 Chemical Risks EN 374-4 Degradation EN 374-5 microorganism tightness EN ISO 21420 protective gloves	Sodium hydroxide Hydrogen Peroxid Formaldehyde 375 The glove is tight a	40% e 30% % against microorganione requirements acc	sms (viral, bacteria a	1420	rding to ISO 16604 -	method B.	KPT 5N 150 134 5-2016 WIRUS
EN 374-1 Chemical Risks EN 374-4 Degradation EN 374-5 microorganism tightness EN ISO 21420 protective gloves EN 455	Sodium hydroxide Hydrogen Peroxid Formaldehyde 375 The glove is tight a	40% e 30% % against microorganione requirements acc	sms (viral, bacteria a	1420	rding to ISO 16604 -	method B.	KPT SN ISO 374-5-2016 WIRUS
EN 374-1 Chemical Risks EN 374-4 Degradation EN 374-5 microorganism tightness EN ISO 21420 protective gloves EN 455 medical gloves for	Sodium hydroxide Hydrogen Peroxid Formaldehyde 375 The glove is tight a The glove meets ti	40% e 30% % against microorganione requirements accome accompanies accome accompanies	sms (viral, bacteria a cording to EN ISO 21 cording to EN 455-1	.420 , EN 455-2, EN 455-3	rding to ISO 16604 -	method B. break ≥ 6 N.	KPT EN 100 374 5-2016 EN 455
EN 374-1 Chemical Risks EN 374-4 Degradation EN 374-5 microorganism tightness EN ISO 21420 protective gloves EN 455 medical gloves for single use	Sodium hydroxide Hydrogen Peroxid Formaldehyde 375 The glove is tight a The glove meets ti	40% e 30% % against microorgani ne requirements acc he requirements acc	sms (viral, bacteria a cording to EN ISO 21 cording to EN 455-1	.420 , EN 455-2, EN 455-3	ording to ISO 16604 -	method B. break ≥ 6 N.	KPT 5N 150 134 5-2016 WIRUS
EN 374-1 Chemical Risks EN 374-4 Degradation EN 374-5 microorganism tightness EN ISO 21420 protective gloves EN 455 medical gloves for single use EN 455-1	Sodium hydroxide Hydrogen Peroxid Formaldehyde 375 The glove is tight a The glove meets ti The glove meets ti	40% e 30% % against microorgani ne requirements acc he requirements acc	sms (viral, bacteria a cording to EN ISO 21 cording to EN 455-1	.420 , EN 455-2, EN 455-3	ording to ISO 16604 -	method B. break ≥ 6 N.	KPT IN NO 224-52016 VIRUS EN 4555
EN 374-1 Chemical Risks EN 374-4 Degradation EN 374-5 microorganism tightness EN ISO 21420 protective gloves EN 455 medical gloves for single use EN 455-1	Sodium hydroxide Hydrogen Peroxid Formaldehyde 375 The glove is tight a The glove meets ti The glove meets ti	40% e 30% % against microorgani ne requirements acc he requirements acc	sms (viral, bacteria a cording to EN ISO 21 cording to EN 455-1	.420 , EN 455-2, EN 455-3	ording to ISO 16604 -	method B. break ≥ 6 N.	KPT IN NO 224-52016 VIRUS EN 4555
EN 374-1 Chemical Risks EN 374-4 Degradation EN 374-5 microorganism tightness EN ISO 21420 protective gloves EN 455 medical gloves for single use EN 455-1 freedom from holes	Sodium hydroxide Hydrogen Peroxid Formaldehyde 375 The glove is tight a The glove meets ti The glove meets ti The glove has an A general Inspection	40% e 30% % against microorgani ne requirements acc he requirements acc	sms (viral, bacteria a cording to EN ISO 21 cording to EN 455-1	.420 , EN 455-2, EN 455-3	ording to ISO 16604 -	method B. break ≥ 6 N.	KPT IN NO 224-52016 VIRUS EN 4555
EN 374-1 Chemical Risks EN 374-4 Degradation EN 374-5 microorganism tightness EN ISO 21420 protective gloves EN 455 medical gloves for single use EN 455-1 freedom from holes EN 16350	Sodium hydroxide Hydrogen Peroxid Formaldehyde 375 The glove is tight a The glove meets ti The glove meets ti The glove has an A general Inspection	40% e 30% % against microorgani ne requirements acc he requirements acc	sms (viral, bacteria a cording to EN ISO 21 cording to EN 455-1	.420 , EN 455-2, EN 455-3	ording to ISO 16604 -	method B. break ≥ 6 N.	KPT IN NO 224-52016 VIRUS EN 4555

QMFORM_60.003 1/3 issue date: 16.04.2025



21423 Winsen (Luhe) - Germany Telefon: +49 (0)4171 / 8480-0

Homepage: www.ampri.de e-mail: info@ampri.de

Technical Data Sheet

Article-No.: 01176

Description: STYLE CEDRO

Nitrile examination glove cedro, non sterile, powder free

LOGISTIC DATA SUBPACKING	
generell information	
material	carton
pieces per subpacking	100
GTIN subpacking size XS	4044941705811
GTIN subpacking size S	4044941705835
GTIN subpacking size M	4044941705859
GTIN subpacking size L	4044941705873
GTIN subpacking size XL	4044941706160
GTIN subpacking size XXL	-
GTIN subpacking size XXXL	-
PZN subpacking size XS	14819614
PZN subpacking size S	14819583
PZN subpacking size M	14819577
PZN subpacking size L	14819560
PZN subpacking size XL	14819608
PZN subpacking size XXL	-
PZN subpacking size XXXL	-
measures & size	
length	215 mm
width	120 mm
heigth	60 mm
weights	
size	gross weight*
XS	380 g
S	410 g
M	430 g
L	460 g
XL	500 g
XXL	-
XXXL	-

LOGISTIC DATA PALETTE				
general information				
kind of palett	euro-palette			
measures & size				
cartons per layer	10			
layers per palette	8			
heigth of the palette	199 cm			
weights				
size	gross weight*			
XS	369 kg			
S	393 kg			
M	409 kg			
L	433 kg			
XL	465 kg			
XXL	-			
XXXL	-			



generell information			
material	carton		
subpackings per outer packing	10		
GTIN outer packing size XS	4044941705828		
GTIN outer packing size S	4044941705842		
GTIN outer packing size M	4044941705866		
GTIN outer packing size L	4044941705880		
GTIN outer packing size XL	4044941706177		
GTIN outer packing size XXL	-		
GTIN outer packing size XXXL	-		
PZN outer packing size XS	-		
PZN outer packing size S	-		
PZN outer packing size M	-		
PZN outer packing size L	-		
PZN outer packing size XL	-		
PZN outer packing size XXL	-		
PZN outer packing size XXXL	-		
measures & size			
length	315 mm		
width	255 mm		
heigth	230 mm		
weights			
size	gross weight*		
XS	4.300 g		
S	4.600 g		
M	4.800 g		
L	5.100 g		
XL	5.500 g		
XXL	-		
XXXL	-		



AMPri Handelsgesellschaft mbH

Benzstraße 16

21423 Winsen (Luhe) - Germany Telefon: +49 (0)4171 / 8480-0

Homepage: www.ampri.de e-mail: info@ampri.de

Technical Data Sheet

Article-No.: 01176

Description: STYLE CEDRO

Nitrile examination glove cedro, non sterile, powder free



WARNINGS AND SAFETY INFORMATION

storage / expiry date

Store gloves in original packaging in a cool and dry place without additional weight, protect from direct sunlight. Do not store near ozone sources (laser printers, copiers). The actual expiry time in use cannot be specified in general terms, as it depends on the general conditions of use. An individual risk assessment must be carried out in each case. The expiry date - valid for proper storage - is stated on the packaging.

use and control

Always use protective gloves only for the intended use and in the correct size. A check/risk assessment must be carried out to ensure that the gloves are suitable for the intended use, as the conditions at the workplace may deviate from those of the type test depending on temperature, abrasion and degradation. Breakthrough times and permeation levels are based on laboratory measurements and are determined using samples taken from the palm of the hand. The actual duration of protection of a glove with a specific substance can vary significantly due to the conditions of use (temperature, abrasion, stretching). In the case of aggressive chemicals, degradation (change in mechanical properties) can be an important factor to consider when selecting chemical-resistant gloves. This information does not reflect the actual duration of protection in the workplace and the distinction between mixtures and pure chemicals. The chemical resistance was determined under laboratory conditions only on the basis of samples from the palm and refers only to the chemicals tested. The situation may be different if the chemical is used in a mixture. The penetration resistance was evaluated under laboratory conditions and refers only to the tested specimen. The degradation results according to EN ISO 374-4 show the change in puncture resistance of the gloves after exposure to the tested chemical.

Before use, the gloves must be checked for holes or damage.

disposal

Used gloves must be disposed of after contact with chemicals in accordance with the disposal regulations for the chemical and the regulations of the local waste disposal company. Unused gloves can be disposed of with household waste.

disinfection

Disinfection is not intended for these gloves and is the responsibility of the user.

warnings/ allergy information Protective gloves are intended for single use only.

This product contains dithiocarbamates, which may cause allergic reactions

donning and doffing instructions











*slight deviations possible due to standard tolerances

rev-no.: 2025-02 date 07.11.2025

changes and errors excepted

QMFORM_60.003 issue date: 16.04.2025