

21423 Winsen (Luhe) - Germany


Telefon: +49 (0)4171 / 8480-0 Homepage: www.ampri.de e-mail: info@ampri.de

Technical Data Sheet

Article-No.: 01177

Description: STYLE Clean Ocean

Nitrile examination glove green, non sterile, powder free





PRODUCT DESCRIP	TION						
material	Latex	✓ Nitrile	□ Vinyl	☐ Vinyl-Nitrile- mixture	Polyethy-lene (PE)	☐ TPE	□ cotton
colour	☐ white	☐ blue	black	☐ mint	☐ purple	☐ mix	
characteristics	☐ prepowdered	powderfree	☐ sterile	non sterile	☑ ambidex-	fits hand-	Aloe Vera
					trous	specific	inner coating
surface	☑ textured	not textured	□ embossed				
SIZES							
	XS (5-6)	S (6-7)	M (7-8)	L (8-9)	XL (9-10)	XXL (10-11)	XXXL (11-12)
width	≤ 80 mm	80 ± 10 mm	95 ± 10 mm	110 ± 10 mm	115 ± 10 mm	-	-
length	≥ 240 mm	≥ 240 mm	≥ 240 mm	≥ 240 mm	≥ 240 mm	-	-
REGULATORY AFFA	IRS						
PPE-Regulation	☐ Category I	☐ Category II	☑ Category III	☐ no PPE-article			
(EU) 2016/425							
MD-Regulation	✓ Class I	☐ Class II a	☐ Class III	□ sterile	☐ measuring	no medical	CE
(EU) 2017/745					function	device	
Food Contact	☑ acidic foods	☑ aqueous	✓ fatty foods	☑ alcoholic	☑ dry foods	not approved	
(EG) 1935/2004		foods		foods		for food-	77
						contact	
STANDARDISATION							
EN 388 Mechanical	abrasion	blade cut	tear resistance	puncture	blade cut	impact tast	
Risks	resistance	resistance	tear resistance	resistance	resistance	impact test	
UISKS							
				resistance			
Level	not applicable	Coupe-Test		resistance	TDM-Test		
Level EN 374-1		Coupe-Test	mical	resistance		letter	
		Coupe-Test cher	mical	resistance	TDM-Test	letter (ISO 374-1/Type B
EN 374-1	not applicable	Coupe-Test cher	mical	resistance	TDM-Test	<	ISO 374-1/Type B
EN 374-1	not applicable Sodium hydroxide	Coupe-Test chei	mical	resistance	TDM-Test code	<	ISO 374-1/Type B
EN 374-1 Chemical Risks	not applicable Sodium hydroxide Hydrogen Peroxide	Coupe-Test chei	mical	resistance	TDM-Test code	(ISO 374-1/Type B
EN 374-1 Chemical Risks EN 374-4	not applicable Sodium hydroxide Hydrogen Peroxide	Coupe-Test chei	mical	Testance	TDM-Test code	(
EN 374-1 Chemical Risks EN 374-4 Degradation	not applicable Sodium hydroxide Hydrogen Peroxide Formaldehyde 379	Coupe-Test chei			code		KPT
EN 374-1 Chemical Risks EN 374-4 Degradation EN 374-5	not applicable Sodium hydroxide Hydrogen Peroxide Formaldehyde 379	Coupe-Test chei			TDM-Test code		KPT 8N 150 374-5-2016
EN 374-1 Chemical Risks EN 374-4 Degradation	not applicable Sodium hydroxide Hydrogen Peroxide Formaldehyde 379	Coupe-Test chei			code		KPT
EN 374-1 Chemical Risks EN 374-4 Degradation EN 374-5 microorganism tightness	not applicable Sodium hydroxide Hydrogen Peroxide Formaldehyde 379 The glove is tight a	cher 40% ≥ 30% 6 gainst microorganis	sms (viral, bacteria a	and fungi). Test acco	code		KPT EN 150 274-5-2016
EN 374-1 Chemical Risks EN 374-4 Degradation EN 374-5 microorganism	not applicable Sodium hydroxide Hydrogen Peroxide Formaldehyde 379 The glove is tight a	Coupe-Test chei	sms (viral, bacteria a	and fungi). Test acco	code		KPT BN 150 274-5-2016
EN 374-1 Chemical Risks EN 374-4 Degradation EN 374-5 microorganism tightness EN ISO 21420 protective gloves	not applicable Sodium hydroxide Hydrogen Peroxide Formaldehyde 379 The glove is tight a	cher 40% 2 30% 6 gainst microorganis	oms (viral, bacteria a	and fungi). Test acco	rding to ISO 16604 -	method B.	KPT EN 150 274-5-2016
EN 374-1 Chemical Risks EN 374-4 Degradation EN 374-5 microorganism tightness EN ISO 21420 protective gloves EN 455	not applicable Sodium hydroxide Hydrogen Peroxide Formaldehyde 379 The glove is tight a	cher 40% 2 30% 6 gainst microorganis	oms (viral, bacteria a	and fungi). Test acco	code	method B.	KPT EN 150 274-5-2016
EN 374-1 Chemical Risks EN 374-4 Degradation EN 374-5 microorganism tightness EN ISO 21420 protective gloves EN 455 medical gloves for	not applicable Sodium hydroxide Hydrogen Peroxide Formaldehyde 379 The glove is tight a	cher 40% 2 30% 6 gainst microorganis	oms (viral, bacteria a	and fungi). Test acco	rding to ISO 16604 -	method B.	KPT EN 150 374-5-2016 VIRUS
EN 374-1 Chemical Risks EN 374-4 Degradation EN 374-5 microorganism tightness EN ISO 21420 protective gloves EN 455 medical gloves for single use	not applicable Sodium hydroxide Hydrogen Peroxide Formaldehyde 379 The glove is tight a The glove meets th	cher 40% 2 30% 6 gainst microorganis ne requirements acco	cording to EN 455-1	and fungi). Test acco	rding to ISO 16604 -	method B. break ≥ 6 N.	KPT EN 150 20-52-20-16 EN 455
EN 374-1 Chemical Risks EN 374-4 Degradation EN 374-5 microorganism tightness EN ISO 21420 protective gloves EN 455 medical gloves for single use EN 455-1	not applicable Sodium hydroxide Hydrogen Peroxide Formaldehyde 379 The glove is tight a The glove meets th The glove meets th	cher 40% 2 30% 6 gainst microorganis ne requirements accorder requ	cording to EN 455-1	and fungi). Test acco	rding to ISO 16604 -	method B. break ≥ 6 N.	KPT KPT KPT KPT KPT KPT KPT KPT
EN 374-1 Chemical Risks EN 374-4 Degradation EN 374-5 microorganism tightness EN ISO 21420 protective gloves EN 455 medical gloves for single use	not applicable Sodium hydroxide Hydrogen Peroxide Formaldehyde 379 The glove is tight a The glove meets th	cher 40% 2 30% 6 gainst microorganis ne requirements accorder requ	cording to EN 455-1	and fungi). Test acco	rding to ISO 16604 -	method B. break ≥ 6 N.	KPT INITIAL DESCRIPTION INIT
EN 374-1 Chemical Risks EN 374-4 Degradation EN 374-5 microorganism tightness EN ISO 21420 protective gloves EN 455 medical gloves for single use EN 455-1 freedom from holes	not applicable Sodium hydroxide Hydrogen Peroxide Formaldehyde 379 The glove is tight a The glove meets th The glove meets th The glove has an A general Inspection	cher 40% 2 30% 6 gainst microorganis ne requirements accorder requ	cording to EN 455-1	and fungi). Test acco	rding to ISO 16604 -	method B. break ≥ 6 N.	KPT KPT KPT KPT KPT KPT KPT KPT
EN 374-1 Chemical Risks EN 374-4 Degradation EN 374-5 microorganism tightness EN ISO 21420 protective gloves EN 455 medical gloves for single use EN 455-1 freedom from holes	not applicable Sodium hydroxide Hydrogen Peroxide Formaldehyde 379 The glove is tight a The glove meets th The glove meets th	cher 40% 2 30% 6 gainst microorganis ne requirements accorder requ	cording to EN 455-1	and fungi). Test acco	rding to ISO 16604 -	method B. break ≥ 6 N.	KPT (N) 150 274-5-2016 (
EN 374-1 Chemical Risks EN 374-4 Degradation EN 374-5 microorganism tightness EN ISO 21420 protective gloves EN 455 medical gloves for single use EN 455-1 freedom from holes	not applicable Sodium hydroxide Hydrogen Peroxide Formaldehyde 379 The glove is tight a The glove meets th The glove meets th The glove has an A general Inspection	cher 40% 2 30% 6 gainst microorganis ne requirements accorder requ	cording to EN 455-1	and fungi). Test acco	rding to ISO 16604 -	method B. break ≥ 6 N.	KPT (N) 150 274-5-2016 (

QMFORM_60.003 issue date: 16.04.2025

EN



21423 Winsen (Luhe) - Germany Telefon: +49 (0)4171 / 8480-0

Homepage: www.ampri.de e-mail: info@ampri.de

Technical Data Sheet

Article-No.: 01177

Description: STYLE Clean Ocean

Nitrile examination glove green, non sterile, powder free

LOGISTIC DATA SUBPACKING	
generell information	
material	carton
pieces per subpacking	100
GTIN subpacking size XS	4044941726564
GTIN subpacking size S	4044941726588
GTIN subpacking size M	4044941726601
GTIN subpacking size L	4044941726625
GTIN subpacking size XL	4044941726649
GTIN subpacking size XXL	-
GTIN subpacking size XXXL	-
PZN subpacking size XS	18062177
PZN subpacking size S	18062160
PZN subpacking size M	18062154
PZN subpacking size L	18062148
PZN subpacking size XL	18062131
PZN subpacking size XXL	-
PZN subpacking size XXXL	-
measures & size	
length	215 mm
width	120 mm
heigth	60 mm
weights	
size	gross weight*
XS	380 g
S	410 g
M	430 g
L	460 g
XL	500 g
XXL	-
XXXL	-

LOGISTIC DATA PALETTE					
general information					
kind of palett	euro-palette				
measures & size					
cartons per layer	10				
layers per palette	8				
heigth of the palette	199 cm				
weights					
size	gross weight*				
XS	369 kg				
S	393 kg				
M	409 kg				
L	433 kg				
XL	465 kg				
XXL	-				
XXXL	-				



LOGISTIC DATA OUTER PACKING generell information			
material	carton		
subpackings per outer packing	10		
GTIN outer packing size XS	4044941726571		
GTIN outer packing size S	4044941726595		
GTIN outer packing size M	4044941726618		
GTIN outer packing size L	4044941726632		
GTIN outer packing size XL	4044941726656		
GTIN outer packing size XXL	-		
GTIN outer packing size XXXL	-		
PZN outer packing size XS	-		
PZN outer packing size S	-		
PZN outer packing size M	-		
PZN outer packing size L	-		
PZN outer packing size XL	-		
PZN outer packing size XXL	-		
PZN outer packing size XXXL	-		
measures & size			
length	315 mm		
width	255 mm		
heigth	230 mm		
weights			
size	gross weight*		
XS	4.300 g		
S	4.600 g		
M	4.800 g		
L	5.100 g		
XL	5.500 g		
XXL	-		
XXXL	-		

EN



AMPri Handelsgesellschaft mbH

Benzstraße 16

21423 Winsen (Luhe) - Germany Telefon: +49 (0)4171 / 8480-0

Homepage: www.ampri.de e-mail: info@ampri.de

Technical Data Sheet

Article-No.: 01177

Description: STYLE Clean Ocean

Nitrile examination glove green, non sterile, powder free



WARNINGS AND SAFETY INFORMATION

storage / expiry date

Store gloves in original packaging in a cool and dry place without additional weight, protect from direct sunlight. Do not store near ozone sources (laser printers, copiers). The actual expiry time in use cannot be specified in general terms, as it depends on the general conditions of use. An individual risk assessment must be carried out in each case. The expiry date - valid for proper storage - is stated on the packaging.

use and control

Always use protective gloves only for the intended use and in the correct size. A check/risk assessment must be carried out to ensure that the gloves are suitable for the intended use, as the conditions at the workplace may deviate from those of the type test depending on temperature, abrasion and degradation. Breakthrough times and permeation levels are based on laboratory measurements and are determined using samples taken from the palm of the hand. The actual duration of protection of a glove with a specific substance can vary significantly due to the conditions of use (temperature, abrasion, stretching). In the case of aggressive chemicals, degradation (change in mechanical properties) can be an important factor to consider when selecting chemical-resistant gloves. This information does not reflect the actual duration of protection in the workplace and the distinction between mixtures and pure chemicals. The chemical resistance was determined under laboratory conditions only on the basis of samples from the palm and refers only to the chemicals tested. The situation may be different if the chemical is used in a mixture. The penetration resistance was evaluated under laboratory conditions and refers only to the tested specimen. The degradation results according to EN ISO 374-4 show the change in puncture resistance of the gloves after exposure to the tested chemical.

Before use, the gloves must be checked for holes or damage.

disposal

Used gloves must be disposed of after contact with chemicals in accordance with the disposal regulations for the chemical and the regulations of the local waste disposal company. Unused gloves can be disposed of with household waste.

disinfection

Disinfection is not intended for these gloves and is the responsibility of the user.

warnings/ allergy information Protective gloves are intended for single use only.

This product contains dithiocarbamates, which may cause allergic reactions

donning and doffing instructions











*slight deviations possible due to standard tolerances

rev-no.: 2025-02 date 07.11.2025

changes and errors excepted

QMFORM_60.003 issue date: 16.04.2025