


21423 Winsen (Luhe) - Germany

Telefon: +49 (0)4171 / 8480-0 Homepage: www.ampri.de e-mail: info@ampri.de

# **Technical Data Sheet**

Article-No.: **01199**Description: **ECO-PLUS** 

Nitrile examination glove white, non sterile, powder free





PRODUCT DESCRIP	TION						
material	☐ Latex	✓ Nitrile	□ Vinyl	☐ Vinyl-Nitrile- mixture	Polyethy-lene (PE)	☐ TPE	cotton
colour	☑ white	☐ blue	☐ black	☐ mint	☐ purple	☐ mix	□ bordeaux
characteristics	prepowdered	powderfree	☐ sterile	non sterile	☑ ambidex-	fits hand-	☐ Aloe Vera
					trous	specific	inner coating
surface	✓ textured	not textured	embossed				
SIZES	(=)	- (0-7)	()	. (2.2)	(5		
	XS (5-6)	S (6-7)	M (7-8)	L (8-9)	XL (9-10)	XXL (10-11)	XXXL (11-12)
width	≤ 80 mm	80 ± 10 mm	95 ± 10 mm	110 ± 10 mm	115 ± 10 mm	-	-
length	≥ 240 mm	≥ 240 mm	≥ 240 mm	≥ 240 mm	≥ 240 mm	-	-
REGULATORY AFFA	AIRS						
PPE-Regulation (EU) 2016/425	☐ Category I	☐ Category II	✓ Category III	☐ no PPE-article			
MD-Regulation	☑ Class I	☐ Class II a	☐ Class III	☐ sterile	☐ measuring	no medical	CE
(EU) 2017/745					function	device	
Food Contact	☑ acidic foods	☑ aqueous		☑ alcoholic	☑ dry foods	not approved	
(EG) 1935/2004		foods		foods		for food-	77
						contact	50.
STANDARDISATION				1	l		
EN 388 Mechanical	abrasion	blade cut	tear resistance	num atuuna	blade cut	insured book	
Risks	resistance	resistance	tear resistance	puncture	resistance	impact test	
THO NO	resistance			resistance			
Level	not applicable	Coupe-Test		resistance	TDM-Test		
		Coupe-Test	nical	resistance		letter	
Level		Coupe-Test	mical	resistance	TDM-Test code	letter	ISO 374-1/Type B
Level EN 374-1	not applicable	Coupe-Test cher	nical	resistance	TDM-Test code	(	ISO 374-1/Type B
Level EN 374-1 Chemical Risks	not applicable  Sodium hydroxide	Coupe-Test  chel	nical	resistance	TDM-Test code	(	ISO 374-1/Type B
Level EN 374-1 Chemical Risks EN 374-4	not applicable  Sodium hydroxide Hydrogen Peroxide	Coupe-Test  chel	nical	resistance	TDM-Test  code	(	ISO 374-1/Type B
Level EN 374-1 Chemical Risks	not applicable  Sodium hydroxide Hydrogen Peroxide	Coupe-Test  chel	mical	resistance	TDM-Test  code	(	
Level EN 374-1 Chemical Risks EN 374-4 Degradation	not applicable  Sodium hydroxide Hydrogen Peroxide Formaldehyde 37%	cher			Code		ISO 374-1/Type B
Level  EN 374-1 Chemical Risks  EN 374-4 Degradation  EN 374-5	not applicable  Sodium hydroxide Hydrogen Peroxide Formaldehyde 37%	cher			TDM-Test  code		KPT 8N NO 374-52016
Level  EN 374-1 Chemical Risks  EN 374-4 Degradation  EN 374-5 microorganism	not applicable  Sodium hydroxide Hydrogen Peroxide Formaldehyde 37%	cher			Code		
Level  EN 374-1 Chemical Risks  EN 374-4 Degradation  EN 374-5 microorganism tightness	not applicable  Sodium hydroxide Hydrogen Peroxide Formaldehyde 37%  The glove is tight a	cher 40% 2 30% 6	ims (viral, bacteria a	and fungi). Test acco	Code		KPT  8N 150 274-5:2016
Level  EN 374-1 Chemical Risks  EN 374-4 Degradation  EN 374-5 microorganism	not applicable  Sodium hydroxide Hydrogen Peroxide Formaldehyde 37%  The glove is tight a	cher	ims (viral, bacteria a	and fungi). Test acco	Code		KPT  (N 150 274-52016
Level  EN 374-1 Chemical Risks  EN 374-4 Degradation  EN 374-5 microorganism tightness  EN ISO 21420 protective gloves	not applicable  Sodium hydroxide Hydrogen Peroxide Formaldehyde 37%  The glove is tight a	cher 40% 2 30% 6 gainst microorganis	ims (viral, bacteria a	and fungi). Test acco	rding to ISO 16604	method B.	KPT  (N 150 274-52016
Level  EN 374-1 Chemical Risks  EN 374-4 Degradation  EN 374-5 microorganism tightness  EN ISO 21420 protective gloves  EN 455	not applicable  Sodium hydroxide Hydrogen Peroxide Formaldehyde 37%  The glove is tight a	cher 40% 2 30% 6 gainst microorganis	ims (viral, bacteria a	and fungi). Test acco	Code	method B.	KPT EN ISO 374-5-2016 VIRUS
Level  EN 374-1 Chemical Risks  EN 374-4 Degradation  EN 374-5 microorganism tightness  EN ISO 21420 protective gloves  EN 455 medical gloves for	not applicable  Sodium hydroxide Hydrogen Peroxide Formaldehyde 37%  The glove is tight a	cher 40% 2 30% 6 gainst microorganis	ims (viral, bacteria a	and fungi). Test acco	rding to ISO 16604	method B.	KPT  EN 150 274-5-2016  VIRUS
Level  EN 374-1 Chemical Risks  EN 374-4 Degradation  EN 374-5 microorganism tightness  EN ISO 21420 protective gloves  EN 455 medical gloves for single use	not applicable  Sodium hydroxide Hydrogen Peroxide Formaldehyde 37%  The glove is tight a  The glove meets th	chere d'accesses de requirements accesses de r	ording to EN ISO 21	and fungi). Test acco	rding to ISO 16604 -	method B.  break ≥ 3.6 N.	KPT  EN 150 324-52016  WIRUS  EN 455
Level  EN 374-1 Chemical Risks  EN 374-4 Degradation  EN 374-5 microorganism tightness  EN ISO 21420 protective gloves  EN 455 medical gloves for single use EN 455-1	not applicable  Sodium hydroxide Hydrogen Peroxide Formaldehyde 37%  The glove is tight a  The glove meets th  The glove meets th	cher 40% 2 30% 6 gainst microorganis ne requirements accome requirements accome	ording to EN ISO 21	and fungi). Test acco	rding to ISO 16604	method B.  break ≥ 3.6 N.	KPT  EN ISO 324-52016  VIRUS  EN 455
Level  EN 374-1 Chemical Risks  EN 374-4 Degradation  EN 374-5 microorganism tightness  EN ISO 21420 protective gloves  EN 455 medical gloves for single use	not applicable  Sodium hydroxide Hydrogen Peroxide Formaldehyde 37%  The glove is tight a  The glove meets th	cher 40% 2 30% 6 gainst microorganis ne requirements accome requirements accome	ording to EN ISO 21	and fungi). Test acco	rding to ISO 16604 -	method B.  break ≥ 3.6 N.	KPT  EN 150 324-52016  WIRUS  EN 455
Level  EN 374-1 Chemical Risks  EN 374-4 Degradation  EN 374-5 microorganism tightness  EN ISO 21420 protective gloves  EN 455 medical gloves for single use EN 455-1	not applicable  Sodium hydroxide Hydrogen Peroxide Formaldehyde 37%  The glove is tight a  The glove meets th  The glove meets th	cher 40% 2 30% 6 gainst microorganis ne requirements accome requirements accome	ording to EN ISO 21	and fungi). Test acco	rding to ISO 16604 -	method B.  break ≥ 3.6 N.	KPT  EN ISO 324-52016  VIRUS  EN 455
Level  EN 374-1 Chemical Risks  EN 374-4 Degradation  EN 374-5 microorganism tightness  EN ISO 21420 protective gloves  EN 455 medical gloves for single use EN 455-1 freedom from holes	not applicable  Sodium hydroxide Hydrogen Peroxide Formaldehyde 37%  The glove is tight a  The glove meets th  The glove meets th  The glove has an A general Inspection	cher 40% 2 30% 6 gainst microorganis ne requirements accome requirements accome	ording to EN ISO 21	and fungi). Test acco	rding to ISO 16604 -	method B.  break ≥ 3.6 N.	KPT  EN ISO 324-52016  VIRUS  EN 455
Level  EN 374-1 Chemical Risks  EN 374-4 Degradation  EN 374-5 microorganism tightness  EN ISO 21420 protective gloves  EN 455 medical gloves for single use EN 455-1 freedom from holes  EN 16350	not applicable  Sodium hydroxide Hydrogen Peroxide Formaldehyde 37%  The glove is tight a  The glove meets th  The glove meets th  The glove has an A general Inspection	cher 40% 2 30% 6 gainst microorganis ne requirements accome requirements accome	ording to EN ISO 21	and fungi). Test acco	rding to ISO 16604 -	method B.  break ≥ 3.6 N.	KPT  EN ISO 324-52016  VIRUS  EN 455

QMFORM\_60.003 issue date: 16.04.2025

**EN** 1/3



21423 Winsen (Luhe) - Germany Telefon: +49 (0)4171 / 8480-0

Homepage: www.ampri.de e-mail: info@ampri.de

## **Technical Data Sheet**

Article-No.: **01199**Description: **ECO-PLUS** 

Nitrile examination glove white, non sterile, powder free

LOGISTIC DATA SUBPACKING			
generell information			
material	carton		
pieces per subpacking	100		
GTIN subpacking size XS	4044941000930		
GTIN subpacking size S	4044941000947		
GTIN subpacking size M	4044941000954		
GTIN subpacking size L	4044941000961		
GTIN subpacking size XL	4044941000978		
GTIN subpacking size XXL	-		
GTIN subpacking size XXXL	-		
PZN subpacking size XS	16902348		
PZN subpacking size S	15622351		
PZN subpacking size M	15622368		
PZN subpacking size L	15622345		
PZN subpacking size XL	15622339		
PZN subpacking size XXL	-		
PZN subpacking size XXXL	-		
measures & size			
length	220 mm		
width	115 mm		
heigth	55 mm		
weights			
size	gross weight*		
XS	400 g		
S	420 g		
M	440 g		
L	470 g		
XL	510 g		
XXL	-		
XXXL	-		

LOGISTIC DATA PALETTE					
general information					
kind of palett	euro-palette				
measures & size					
cartons per layer	10				
layers per palette	8				
heigth of the palette	205 cm				
weights					
size	gross weight*				
XS	385 kg				
S	401 kg				
M	417 kg				
L	441 kg				
XL	473 kg				
XXL	-				
XXXL	-				

EN



LOGISTIC DATA OUTER PACKING			
generell information			
material	carton		
subpackings per outer packing	10		
GTIN outer packing size XS	4044941002477		
GTIN outer packing size S	4044941002484		
GTIN outer packing size M	4044941002491		
GTIN outer packing size L	4044941002507		
GTIN outer packing size XL	4044941002514		
GTIN outer packing size XXL	-		
GTIN outer packing size XXXL	-		
PZN outer packing size XS	-		
PZN outer packing size S	-		
PZN outer packing size M	-		
PZN outer packing size L	-		
PZN outer packing size XL	-		
PZN outer packing size XXL	-		
PZN outer packing size XXXL	-		
measures & size			
length	290 mm		
width	240 mm		
heigth	237 mm		
weights			
size	gross weight*		
XS	4.500 g		
S	4.700 g		
M	4.900 g		
L	5.200 g		
XL	5.600 g		
XXL	-		
XXXL	-		



## AMPri Handelsgesellschaft mbH

Benzstraße 16

21423 Winsen (Luhe) - Germany Telefon: +49 (0)4171 / 8480-0

Homepage: www.ampri.de e-mail: info@ampri.de

## **Technical Data Sheet**

Article-No.: **01199**Description: **ECO-PLUS** 

Nitrile examination glove white, non sterile, powder free



## WARNINGS AND SAFETY INFORMATION

storage /	expiry
date	

Store gloves in original packaging in a cool and dry place without additional weight, protect from direct sunlight. Do not store near ozone sources (laser printers, copiers). The actual expiry time in use cannot be specified in general terms, as it depends on the general conditions of use. An individual risk assessment must be carried out in each case. The expiry date - valid for proper storage - is stated on the packaging.

#### use and control

Always use protective gloves only for the intended use and in the correct size. A check/risk assessment must be carried out to ensure that the gloves are suitable for the intended use, as the conditions at the workplace may deviate from those of the type test depending on temperature, abrasion and degradation. Breakthrough times and permeation levels are based on laboratory measurements and are determined using samples taken from the palm of the hand. The actual duration of protection of a glove with a specific substance can vary significantly due to the conditions of use (temperature, abrasion, stretching). In the case of aggressive chemicals, degradation (change in mechanical properties) can be an important factor to consider when selecting chemical-resistant gloves. This information does not reflect the actual duration of protection in the workplace and the distinction between mixtures and pure chemicals. The chemical resistance was determined under laboratory conditions only on the basis of samples from the palm and refers only to the chemicals tested. The situation may be different if the chemical is used in a mixture. The penetration resistance was evaluated under laboratory conditions and refers only to the tested specimen. The degradation results according to EN ISO 374-4 show the change in puncture resistance of the gloves after exposure to the tested chemical.

Before use, the gloves must be checked for holes or damage.

## disposal

Used gloves must be disposed of in accordance with the disposal regulations of the local waste disposal company. Unused gloves can be disposed of with household waste.

## disinfection

Disinfection is not intended for these gloves and is the responsibility of the user.

### warnings/ allergy information

Protective gloves are intended for single use only.

This product contains dithiocarbamates, which may cause allergic reactions

# donning and doffing instructions











\*slight deviations possible due to standard tolerances

rev-no.: 2025-01 date 16.06.2025

changes and errors excepted

QMFORM\_60.003 issue date: 16.04.2025