

Telefon: +49 (0)4171 / 8480-0 Homepage: www.ampri.de e-mail: info@ampri.de




# **Technical Data Sheet**

Article-No.: 120-020

EN

Description: pura comfort white

Nitrile examination glove white, non sterile, powder free





PRODUCT DESCRIP	TION						
material	Latex	✓ Nitrile	□ Vinyl	☐ Vinyl-Nitrile- mixture	Polyethy-lene (PE)	☐ TPE	Cotton
colour	☑ white	☐ blue	□ black	☐ mint	purple	mix	□ bordeaux
characteristics	☐ prepowdered	powderfree	☐ sterile	non sterile	☑ ambidex-	☐ fits hand-	☐ Aloe Vera
					trous	specific	inner coating
surface	✓ textured	not textured	☐ embossed				_
SIZES			()		(2 )		
	XS (5-6)	S (6-7)	M (7-8)	L (8-9)	XL (9-10)	XXL (10-11)	XXXL (11-12)
width	≤ 80 mm	80 ± 10 mm	95 ± 10 mm	110 ± 10 mm	115 ± 10 mm	-	-
length	≥ 240 mm	≥ 240 mm	≥ 240 mm	≥ 240 mm	≥ 240 mm	-	-
REGULATORY AFFA							
PPE-Regulation (EU) 2016/425	☐ Category I	☐ Category II	✓ Category III	□ no PPE-article			66
MD-Regulation	☑ Class I	Class II a	Class III	□ sterile	☐ measuring	no medical	CE
(EU) 2017/745					function	device	
Food Contact	☑ acidic foods	☑ aqueous		☑ alcoholic	☑ dry foods	☐ not approved	
(EG) 1935/2004		foods		foods		for food-	527
						contact	
STANDARDISATION	1						
EN 388 Mechanical	abrasion	blade cut	tear resistance	puncture	blade cut	impact test	
Risks	resistance	resistance	tear resistance	resistance	resistance	impact test	
Misks	resistance	Coupe-Test		resistance	TDM-Test		
Level	not applicable	coupe-rest			TDIVI-TCSC		
EN 374-1	chemical code letter					letter	
Chemical Risks	Sodium hydroxide		incui		K		ISO 374-1/Type B
Chemical Risks				P		130 374 171790 8	
EN 274 4	Hydrogen Peroxide	≥ 3()%			1	,	
	Hydrogen Peroxide						
EN 374-4	Hydrogen Peroxide Formaldehyde 37%				F		
Degradation							
							KPT KPT
	Formaldehyde 37%	6	ms (viral, bacteria a	and fungi). Test acco	7	Γ	EN ISO 374-5:2016
Degradation EN 374-5	Formaldehyde 37%	6	ms (viral, bacteria a	and fungi). Test acco	7	Γ	EN ISO 374-5:2016
Degradation	Formaldehyde 37%	6	ms (viral, bacteria a	and fungi). Test acco	7	Γ	
Degradation EN 374-5 microorganism tightness	Formaldehyde 37% The glove is tight a	6 gainst microorganis			7	Γ	EN ISO 374-5:2016
EN 374-5 microorganism tightness	Formaldehyde 37% The glove is tight a	6			7	Γ	EN ISO 374-5:2016
Degradation EN 374-5 microorganism tightness	Formaldehyde 37% The glove is tight a	6 gainst microorganis			7	Γ	EN ISO 374-5:2016
EN 374-5 microorganism tightness	The glove is tight a	gainst microorganis	ording to EN ISO 21	420	ording to ISO 16604 -	method B.	EN 150 274-5:2016
Degradation  EN 374-5 microorganism tightness  EN ISO 21420 protective gloves  EN 455	The glove is tight a	gainst microorganis	ording to EN ISO 21		ording to ISO 16604 -	method B.	EN 150 374-52016
EN 374-5 microorganism tightness EN ISO 21420 protective gloves EN 455 medical gloves for	The glove is tight a	gainst microorganis	ording to EN ISO 21	420	ording to ISO 16604 -	method B.	8N 150 374-52016
EN 374-5 microorganism tightness EN ISO 21420 protective gloves EN 455 medical gloves for single use	The glove is tight a  The glove meets th	gainst microorganis ne requirements acc ne requirements acc	ording to EN ISO 21 ording to EN 455-1,	.420 .EN 455-2, EN 455-3	ording to ISO 16604 -	method B.	N 150 274-52016  VIRUS  EN 455
EN 374-5 microorganism tightness EN ISO 21420 protective gloves EN 455 medical gloves for single use EN 455-1	The glove meets the The glove has an A	gainst microorganis ne requirements acc ne requirements acc	ording to EN ISO 21 ording to EN 455-1,	420	ording to ISO 16604 -	method B.	EN 455
EN 374-5 microorganism tightness EN ISO 21420 protective gloves EN 455 medical gloves for single use	The glove is tight a  The glove meets th	gainst microorganis ne requirements acc ne requirements acc	ording to EN ISO 21 ording to EN 455-1,	.420 .EN 455-2, EN 455-3	ording to ISO 16604 -	method B.	EN 455
EN 374-5 microorganism tightness EN ISO 21420 protective gloves EN 455 medical gloves for single use EN 455-1 freedom from holes	The glove meets the glove meets the glove meets the glove has an Ageneral Inspection	gainst microorganis ne requirements acc ne requirements acc	ording to EN ISO 21 ording to EN 455-1,	.420 .EN 455-2, EN 455-3	ording to ISO 16604 -	method B.	EN 455
EN 374-5 microorganism tightness EN ISO 21420 protective gloves EN 455 medical gloves for single use EN 455-1 freedom from holes	The glove meets the The glove has an A	gainst microorganis ne requirements acc ne requirements acc	ording to EN ISO 21 ording to EN 455-1,	.420 .EN 455-2, EN 455-3	ording to ISO 16604 -	method B.	EN 455
EN 374-5 microorganism tightness EN ISO 21420 protective gloves EN 455 medical gloves for single use EN 455-1 freedom from holes	The glove meets the glove meets the glove meets the glove has an Ageneral Inspection	gainst microorganis ne requirements acc ne requirements acc	ording to EN ISO 21 ording to EN 455-1,	.420 .EN 455-2, EN 455-3	ording to ISO 16604 -	method B.	EN 455

QMFORM\_60.003 1/3



21423 Winsen (Luhe) - Germany Telefon: +49 (0)4171 / 8480-0

Homepage: www.ampri.de e-mail: info@ampri.de

# **Technical Data Sheet**

Article-No.: **120-020** 

Description: pura comfort white

Nitrile examination glove white, non sterile, powder free

LOGISTIC DATA SUBPACKING			
generell information			
material	carton		
pieces per subpacking	100		
GTIN subpacking size XS	4044941009742		
GTIN subpacking size S	4044941009759		
GTIN subpacking size M	4044941009766		
GTIN subpacking size L	4044941009773		
GTIN subpacking size XL	4044941009780		
GTIN subpacking size XXL	-		
GTIN subpacking size XXXL	-		
PZN subpacking size XS	13511334		
PZN subpacking size S	13511363		
PZN subpacking size M	13511311		
PZN subpacking size L	13511305		
PZN subpacking size XL	13511328		
PZN subpacking size XXL	-		
PZN subpacking size XXXL	-		
measures & size			
length	200 mm		
width	110 mm		
heigth	50 mm		
weights			
size	gross weight*		
XS	300 g		
S	330 g		
M	360 g		
L	390 g		
XL	420 g		
XXL	-		
XXXL	-		

LOGISTIC DATA PALETTE	
general information	
kind of palett	euro-palette
measures & size	
cartons per layer	14
layers per palette	9
heigth of the palette	204 cm
weights	
size	gross weight*
XS	466 kg
S	504 kg
M	542 kg
L	579 kg
XL	617 kg
XXL	-
XXXL	-



LOGISTIC DATA OUTER PACKING			
generell information			
material	carton		
subpackings per outer packing	10		
GTIN outer packing size XS	4044941009797		
GTIN outer packing size S	4044941009803		
GTIN outer packing size M	4044941009810		
GTIN outer packing size L	4044941009827		
GTIN outer packing size XL	4044941009834		
GTIN outer packing size XXL	-		
GTIN outer packing size XXXL	-		
PZN outer packing size XS	-		
PZN outer packing size S	-		
PZN outer packing size M	-		
PZN outer packing size L	-		
PZN outer packing size XL	-		
PZN outer packing size XXL	-		
PZN outer packing size XXXL	-		
measures & size			
length	260 mm		
width	230 mm		
heigth	210 mm		
weights			
size	gross weight*		
XS	3.500 g		
S	3.800 g		
M	4.100 g		
L	4.400 g		
XL	4.700 g		
XXL	-		
XXXL	-		



## AMPri Handelsgesellschaft mbH

Benzstraße 16

21423 Winsen (Luhe) - Germany Telefon: +49 (0)4171 / 8480-0

Homepage: www.ampri.de e-mail: info@ampri.de

## **Technical Data Sheet**

Article-No.: 120-020

Description: pura comfort white

Nitrile examination glove white, non sterile, powder free



### WARNINGS AND SAFETY INFORMATION

storage /	expiry
date	

Store gloves in original packaging in a cool and dry place without additional weight, protect from direct sunlight. Do not store near ozone sources (laser printers, copiers). The actual expiry time in use cannot be specified in general terms, as it depends on the general conditions of use. An individual risk assessment must be carried out in each case. The expiry date - valid for proper storage - is stated on the packaging.

#### use and control

Always use protective gloves only for the intended use and in the correct size. A check/risk assessment must be carried out to ensure that the gloves are suitable for the intended use, as the conditions at the workplace may deviate from those of the type test depending on temperature, abrasion and degradation. Breakthrough times and permeation levels are based on laboratory measurements and are determined using samples taken from the palm of the hand. The actual duration of protection of a glove with a specific substance can vary significantly due to the conditions of use (temperature, abrasion, stretching). In the case of aggressive chemicals, degradation (change in mechanical properties) can be an important factor to consider when selecting chemical-resistant gloves. This information does not reflect the actual duration of protection in the workplace and the distinction between mixtures and pure chemicals. The chemical resistance was determined under laboratory conditions only on the basis of samples from the palm and refers only to the chemicals tested. The situation may be different if the chemical is used in a mixture. The penetration resistance was evaluated under laboratory conditions and refers only to the tested specimen. The degradation results according to EN ISO 374-4 show the change in puncture resistance of the gloves after exposure to the tested chemical.

Before use, the gloves must be checked for holes or damage.

## disposal

Used gloves must be disposed of after contact with chemicals in accordance with the disposal regulations for the chemical and the regulations of the local waste disposal company. Unused gloves can be disposed of with household waste.

## disinfection

Disinfection is not intended for these gloves and is the responsibility of the user.

#### warnings/ allergy information

Protective gloves are intended for single use only.

This product contains dithiocarbamates, which may cause allergic reactions

# donning and doffing instructions











\*slight deviations possible due to standard tolerances

rev-no.: 2025-02 date 07.11.2025

changes and errors excepted

QMFORM\_60.003 issue date: 16.04.2025