AMPri Handelsgesellschaft mbH
Benzstraße 16
21423 Winsen (Luhe) - Germany
Telefon: +49 (0)4171 / 8480-0
Homepage: www.ampri.de
e-mail: info@ampri.de

Technical Data Sheet



Article-No.: **AL-002**

Description: **ALPHA-EXTREME GRIP**
Nitrile glove
black, non sterile, powder free

THICKNESS*		
cuff	**palm**	**fingertips**
0,08 mm	0,15 mm	0,17 mm

PRODUCT DESCRIPTION							
material	☐ Latex	☑ Nitrile	☐ Vinyl	☐ Vinyl-Nitrile-mixture	☐ Polyethy-lene (PE)	☐ TPE	☐ cotton
colour	☐ white	☐ blue	☑ black	☐ mint	☐ purple	☐ mix	☐ transparent
characteristics	☐ prepowdered	☑ powderfree	☐ sterile	☑ non sterile	☑ ambidex-trous	☐ fits hand-specific	☐ cotton flocked
surface	☑ textured	☐ not textured	☐ embossed				

SIZES							
	XS (5-6)	**S (6-7)**	**M (7-8)**	**L (8-9)**	**XL (9-10)**	**XXL (10-11)**	**XXXL (11-12)**
width	-	80 ± 10 mm	95 ± 10 mm	110 ± 10 mm	115 ± 10 mm	125 ± 10 mm	-
length	-	≥ 240 mm	≥ 240 mm	≥ 240 mm	≥ 240 mm	≥ 240 mm	-

REGULATORY AFFAIRS							
PPE-Regulation (EU) 2016/425	☐ Category I	☐ Category II	☑ Category III	☐ no PPE-article			CE
MD-Regulation (EU) 2017/745	☑ Class I	☐ Class II a	☐ Class III	☐ sterile	☐ measuring function	☐ no medical device	
Food Contact (EG) 1935/2004	☑ acidic foods	☑ aqueous foods	☑ fatty foods	☑ alcoholic foods	☑ dry foods	☐ not approved for food-contact	

STANDARDISATION							
EN 388 Mechanical Risks	**abrasion resistance**	**blade cut resistance Coupe-Test**	**tear resistance**	**puncture resistance**	**blade cut resistance TDM-Test**	**impact test**	
Level	not applicable						

	chemical	**code letter**	
EN 374-1 Chemical Risks	Sodium hydroxide 40%	K	ISO 374-1/Type B
	Hydrogen Peroxide 30%	P	
EN 374-4 Degradation	Formaldehyde 37%	T	KPT

EN 374-5 microorganism tightness	The glove is tight against microorganisms (viral, bacteria and fungi). Test according to ISO 16604 - method B.
EN ISO 21420 protective gloves	The glove meets the requirements according to EN ISO 21420
EN 455 medical gloves for single use	The glove meets the requirements according to EN 455-1, EN 455-2, EN 455-3, EN 455-4. Force at break ≥ 6 N.
EN 455-1 freedom from holes	The glove has an AQL < 1.5 in regards to the water retention test (sampling inspection in acc. to ISO 2859-1, general Inspection Level I)
EN 16350 electrostatic properties	not applicable

AMPri Handelsgesellschaft mbH
Benzstraße 16
21423 Winsen (Luhe) - Germany
Telefon: +49 (0)4171 / 8480-0
Homepage: www.ampri.de
e-mail: info@ampri.de

Technical Data Sheet

Article-No.: **AL-002**

Description: **ALPHA-EXTREME GRIP**
Nitrile glove
black, non sterile, powder free



LOGISTIC DATA SUBPACKING	
generell information	
material	carton
pieces per subpacking	100
GTIN subpacking size XS	-
GTIN subpacking size S	4044941763262
GTIN subpacking size M	4044941763286
GTIN subpacking size L	4044941763309
GTIN subpacking size XL	4044941763323
GTIN subpacking size XXL	4044941763347
GTIN subpacking size XXXL	-
PZN subpacking size XS	-
PZN subpacking size S	-
PZN subpacking size M	-
PZN subpacking size L	-
PZN subpacking size XL	-
PZN subpacking size XXL	-
PZN subpacking size XXXL	-
measures & size	
length	205 mm
width	115 mm
heigth	65 mm
weights	
size	**gross weight***
XS	-
S	630 g
M	710 g
L	770 g
XL	850 g
XXL	930 g
XXXL	-

LOGISTIC DATA OUTER PACKING	
generell information	
material	carton
subpackings per outer packing	10
GTIN outer packing size XS	-
GTIN outer packing size S	4044941763279
GTIN outer packing size M	4044941763293
GTIN outer packing size L	4044941763316
GTIN outer packing size XL	4044941763330
GTIN outer packing size XXL	4044941763354
GTIN outer packing size XXXL	-
PZN outer packing size XS	
PZN outer packing size S	-
PZN outer packing size M	-
PZN outer packing size L	-
PZN outer packing size XL	-
PZN outer packing size XXL	-
PZN outer packing size XXXL	-
measures & size	
length	340 mm
width	240 mm
heigth	220 mm
weights	
size	**gross weight***
XS	-
S	6.800 g
M	7.600 g
L	8.200 g
XL	9.000 g
XXL	9.800 g
XXXL	-

LOGISTIC DATA PALETTE	
general information	
kind of palett	euro-palette
measures & size	
cartons per layer	6
layers per palette	5
heigth of the palette	125 cm
weights	
size	**gross weight***
XS	-
S	229 kg
M	253 kg
L	271 kg
XL	295 kg
XXL	319 kg
XXXL	-

AMPri Handelsgesellschaft mbH
Benzstraße 16
21423 Winsen (Luhe) - Germany
Telefon: +49 (0)4171 / 8480-0
Homepage: www.ampri.de
e-mail: info@ampri.de

Technical Data Sheet

Article-No.: **AL-002**
Description: **ALPHA-EXTREME GRIP**
Nitrile glove
black, non sterile, powder free



WARNINGS AND SAFETY INFORMATION


storage / expiry date	Store gloves in original packaging in a cool and dry place without additional weight, protect from direct sunlight. Do not store near ozone sources (laser printers, copiers). The actual expiry time in use cannot be specified in general terms, as it depends on the general conditions of use. An individual risk assessment must be carried out in each case. The expiry date - valid for proper storage - is stated on the packaging.

use and control	Always use protective gloves only for the intended use and in the correct size. A check/risk assessment must be carried out to ensure that the gloves are suitable for the intended use, as the conditions at the workplace may deviate from those of the type test depending on temperature, abrasion and degradation. Breakthrough times and permeation levels are based on laboratory measurements and are determined using samples taken from the palm of the hand. The actual duration of protection of a glove with a specific substance can vary significantly due to the conditions of use (temperature, abrasion, stretching). In the case of aggressive chemicals, degradation (change in mechanical properties) can be an important factor to consider when selecting chemical-resistant gloves. This information does not reflect the actual duration of protection in the workplace and the distinction between mixtures and pure chemicals. The chemical resistance was determined under laboratory conditions only on the basis of samples from the palm and refers only to the chemicals tested. The situation may be different if the chemical is used in a mixture. The penetration resistance was evaluated under laboratory conditions and refers only to the tested specimen. The degradation results according to EN ISO 374-4 show the change in puncture resistance of the gloves after exposure to the tested chemical. Before use, the gloves must be checked for holes or damage.

disposal	Used gloves must be disposed of in accordance with the disposal regulations of the local waste disposal company. Unused gloves can be disposed of with household waste.

disinfection	Disinfection is not intended for these gloves and is the responsibility of the user.

warnings	Protective gloves are intended for single use only.

donning and doffing instructions	

*slight deviations possible due to standard tolerances

rev-no.: 2026-01
date 15.10.2026

changes and errors excepted